



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product Name PRO PLASTER PRO HANDIMAN RANGE ALL PURPOSE JOINTING COMPOUND

Synonyms MULTIPURPOSE DIY PAI, 4TPL-DIY

1.2 Uses and uses advised against

Uses: Jointing compound for plasterboard

1.3 Details of the supplier of the product

Supplier Name PRO PLASTER PRODUCTS

Address 31 Neumann Rd, Capalaba, QLD, 4157, AUSTRALIA

Telephone 1800 652 267; +61 (7) 3906 4200

Fax +61 (7) 3390 3281

Email sales@proplaster.com.au

Website <http://www.proplaster.com.au>

1.4 Emergency telephone numbers

Emergency 13 11 26 (Poisons Information Centre)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
LIMESTONE (CALCIUM CARBONATE)	1317-65-3	215-279-6	<50%
ATTAPULGITE CLAY (PALYGORSKITE)	12174-11-7	601-805-5	<3%
2,2',2''-(HEXAHYDRO-1,3,5-TRIAZINE-1,3,5-TRIYL)TRIETHANOL	4719-04-4	225-208-0	<1%
HYDROXYETHYL CELLULOSE	9004-62-0	618-387-5	<1%
WATER	7732-18-5	686-299-4	Remainder
NON-HAZARDOUS INGREDIENTS	Not Available	Not Available	<10%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

PRODUCT NAME: PRO PLASTER 4T JOINTING COMPOUND

- Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
- Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form. Rinse mouth out with water and give plenty of water to drink.
- First aid facilities** Normal washroom facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing Media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

5.3 Advice for firefighters

No fire or explosion hazard exists.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible. Alternatively, contain spillage, then collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for Safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Calcium carbonate (Limestone, Marble, Whiting)	SWA [AUS]	--	10	--	--
Nuisance dust	SWA [AUS]	--	10	--	--

8.1 Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well-ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE

Eye / Face	Wear safety glasses
Hands	Wear PVC or rubber gloves
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	If sanding dry product, wear a Class P1 (particulate) / N95 respirator



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	OFF WHITE TO CREAM PASTE
Odour	NEUTRAL ODOUR
Flammability	NON FLAMMABLE
Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILBLE
Melting Point	NOT AVAILBLE
Evaporation Rate	NOT AVAILBLE
pH	9.5 (Approximately)
Vapour Density	NOT AVAILBLE
Relative density	NOT AVAILBLE
Solubility (Water)	SOLUBLE
Vapour Pressure	NOT AVAILBLE
Upper explosion Limit	NOT RELEVANT
Lower Explosion Limit	NOT RELEVANT
Partition Coefficient	NOT AVAILBLE
Autoignition Temperature	NOT AVAILBLE
Decomposition temperature	NOT AVAILBLE
Viscosity	NOT AVAILBLE
Explosive properties	NOT AVAILBLE
Oxidising properties	NOT AVAILBLE
Odour threshold	NOT AVAILBLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Calcium carbonate reacts with acids and acidic salts to generate gaseous carbon dioxide with effervescence (bubbling). The reaction with concentrated solutions of acids is rapid and exothermic. The effervescence can create extensive foaming. Ignites on contact with fluorine.

PRODUCT NAME: PRO PLASTER 4T JOINTING COMPOUND**10.1 Chemical stability**

Stable under recommended conditions of storage.

10.2 Possibility of hazardous reactions

Polymerization will not occur.

10.3 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.4 Incompatible materials

Incompatible with acids (e.g. nitric acid), fluorine, aluminium (hot) and ammonium salts.

10.5 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

This product is expected to be of low acute toxicity. Under normal conditions of use, adverse health effects are not anticipated. Ingestion of large amounts may cause gastrointestinal disturbances.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
LIMESTONE (CALCIUM CARBONATE)	> 5000 mg/kg (rat)	--	--
2,2',2''-(HEXAHYDRO-1,3,5-TRIAZINE-1,3,5-TRIYL)TRIETHANOL	763 mg/kg (rat)	> 2000 mg/kg (rat)	--

Skin Contact may result in mild irritation, rash and dermatitis.

Eye Contact may result in mild irritation, lacrimation and redness

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen. Attapulgitic clay has been classified by IARC as Group 2B (possibly carcinogenic to humans) when present as long respirable fibres. In this product, attapulgitic is incorporated in a paste matrix and is not expected to be present as respirable fibres under normal conditions of use.

Reproductive Not classified as a reproductive toxin

STOT – single exposure Not classified as causing organ damage from single exposure

STOT – repeated exposure Not classified as causing organ damage from repeated exposure

Aspiration Not relevant.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Calcium carbonate occurs naturally in a wide variety of substances including limestone, marble and egg shells. It is not anticipated to cause adverse environmental effects.

12.2 Persistence and degradability

Dissolved calcium carbonate dissociates into calcium and carbonate ions. Calcium ions will be assimilated by living organisms in the water and the carbonate will become part of the carbon cycle.

12.3 Bioaccumulative potential

This product does not bioaccumulate.

12.4 Mobility in soil

Due to its limited solubility, calcium carbonate precipitates and deposits on the sediment.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

PRODUCT NAME: PRO PLASTER 4T JOINTING COMPOUND**13.1 Waste disposal Legislation**

For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.1 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.2 Transport hazard class	None allocated.	None allocated.	None allocated.
14.3 Packing Group	None allocated.	None allocated.	None allocated.

14.4 Environmental hazards

Not a Marine Pollutant.

14.5 Special precautions for user

Hazchem code None allocated.

15 REGULATORY INFORMATION

Poison Schedule

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications

Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

Inventory listings

AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)

All components are listed on AIIC, or are exempt.

16 OTHER INFORMATION

Additional information

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use, quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PRODUCT NAME: PRO PLASTER 4T JOINTING COMPOUND

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Meter
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmtglobal.com
Web: www.rmtglobal.com

[End of SDS]